

## MEASURES ULTRAVIOLET RADIATION.

### DESCRIPTION

The ultraviolet meter measures and displays instantaneous readings of the ultraviolet radiation between 250 and 400 nanometers (nm) in  $\mu\text{mol m}^{-2} \text{s}^{-1}$  (micromols of photons per square meter per second) or Watts. The self-cleaning dome-shaped head of the MU-200 prevents water accumulation. The sensor head is potted solid to prevent internal condensation in humid environments.

Although the relative wavelengths of UV radiation differ among sunlight and electric lights, our measurements indicate that this sensor provides a close estimate of the UV radiation coming from electric lamps. This meter is particularly useful for determining the UV filtering capacity of the transparent plastic and glass barriers that are commonly used below electric lamps.

Each meter can store up to 99 manually recorded measurements. In automatic mode, measurements are made every 30 seconds and averages are stored every 30 minutes. Daily totals are also calculated and the past 99 days are recorded. The AC-100 communication cable must be purchased to download data to a PC.



(SMPL) 99 Sample Measurements	(LOG) 99 Log Measurements	(LOG) 99 Daily Total Measurements
Viewable on meter LCD & downloadable		Downloadable Only

### RECOMMENDED ACCESSORIES



**AL-100** A leveling plate used to keep meters with separate sensor level. (MQ-200)



**AL-210** Leveling plate and mounting base for meters with integral sensor.



**AC-100** Communication cable is required for data download to a computer.

## SPECIFICATIONS

### MEMORY

- 99 manually stored data points
- Automatically store 99 consecutive 30 minute averages
- 99 daily averages

### MEMORY

- 99 manually stored data points
- Automatically store 99 consecutive 30 minute averages

### RANGE

- 0 - 199.9  $\mu\text{mol m}^{-2} \text{s}^{-1}$  (full UV in sunlight; 170  $\mu\text{mol m}^{-2} \text{s}^{-1}$ )

### ABSOLUTE ACCURACY

- $\pm 10\%$

### INPUT POWER

- Standard 3 V coin cell battery

### MASS

- MU-100: 150 g
- MU-200: 180 g

### LONG-TERM DRIFT

- Less than 3% per year

### OPERATING ENVIRONMENT

- 0 to 50° C
- Less than 90% non-condensing, relative humidity up to 30 C
- Less than 70% relative humidity from 30 to 50° C

### DISPLAY

- 4.2 by 2.8 cm

### CABLE (MU-200 SERIES)

- 2 meters of twisted-pair wire
- Shielded w/ Santoprene casing
- Longer cable lengths are available in multiples of 5 meters

### WARRANTY

- 1 year against defects in materials and workmanship

## MEASUREMENTS

